

RAINSAVER PLUG N' PLAY PUMP

The Rainsaver Plug N' Play Pump supplies clean rainwater from a rainwater tank via an automatic pressure system to pump toilets, laundry, and garden taps in a household.



PUMP WITH SLATE GREY COVER



PUMP WITHOUT COVER

The Rainsaver Plug N Play Pump is connected to both water tank and mains water supply. A float switch is included on the pump which prevents the pump from running dry and allow automatic switch over to mains, should the rainwater tank level be too low and/or there is a power shortage.

/ PUMP SPECIFICATIONS

GENERAL PUMP SPECIFICATIONS	
Maximum Recommended Continuous Pump Flow	58L/min @ 0m head
Maximum Recommended Pump Pressure	395 kPa
Maximum Operating Pressure	6 bar
Maximum Head	30m (20L/min)
ELECTRICAL PUMP SPECIFICATIONS	
Current	3.5 amps
Rated Voltage	220-240V
Mains Frequency	50Hz

/ PUMP REQUIREMENTS

- Minimum 25mm suction line from the tank to the pump.
- Minimum 20mm water feed line from the cold-water mains to the pump.
- Minimum 20mm lilac water feed lined to reuse requirements (laundry, toilets, and hose taps).
- All reuse hose taps should be labelled with a non-potable water sign.

/ BENEFITS

AUTOMATIC SWITCHOVER

Automatically switches between tank and mains water supply.

WEATHER PROOF

Pump comes with a pump cover for further protection from the elements.

DAMAGE PROTECTION

Pump features a rainsaver auto changeover device and a low level float to prevent the pump from running dry.

BACKFLOW PREVENTION

In-built testable backflow prevention device to prevent contamination to the potable water network.

DURABLE

Corrosion-resistant pump body diffuser and impeller to ensure pump durability

/ COVER COLOUR

Slate Grey kept in stock, beige available upon request.

Please Note: Colours may not be 100% accurate.



SLATE GREY



BEIGE